



## INSTALLATION METHOD FOR HEAD STUD KITS

Part Number: AR8696 Application: Yamaha YXZ - CA625+

1. **Always verify the part number for your application with the part number on the side of box and the part number on the instruction sheet. This will help ensure you have the correct installation procedure for your specific application before installing any components.**
2. Clean and inspect all hardware prior to installation. Look for obvious defects or shipping damages, plus proper fit, length and dimension.
3. To ensure proper thread engagement and accurate torque readings, clean ALL threads in the block. Chase if necessary with ARP Thread Chaser.
4. Screw studs into the block "HAND TIGHT ONLY".  
**NOTE: LOCTITE MAY BE USED IF A PERMANENT MOUNTING OF THE STUDS IS PREFERRED.**
5. Install the cylinder head(s) and check for binding or misalignment.
6. Lubricate the stud threads and nuts with ARP Ultra Torque lube (provided). Do not lubricate underside of washers. Then install the washers and the nuts onto the studs and tighten them hand tight. **ARP recommends using the ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT that is provided with each kit as opposed to motor oil. This is due to higher friction on the studs as well as inconsistencies in the clamping force of the fasteners when motor oil or other low quality lubricants are used.**

### TORQUE PROCEDURE

7. Following the manufacturers recommended torque sequence tighten the nuts in three equal steps to 65 ft lbs with **ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT.**

- |  |
|--|
| <ol style="list-style-type: none"> <li>1. Tighten nuts to 15 ft-lbs</li> <li>2. Tighten nuts to 30 ft-lbs</li> <li>3. Tighten nuts to 65 ft-lbs</li> </ol> |
|--|

ARP Ultra-Torque Fastener Assembly Lubricant has been specifically designed to reduce tension preload scatter and eliminate the need to cycle high performance engine fasteners before final installation. ARP Ultra-Torque far surpasses all requirements offered by previous ARP lubricants in terms of fastener preload repeatability and performance lubricating properties. For more information on ARP Ultra-Torque visit the ARP website at [www.arp-bolts.com](http://www.arp-bolts.com)



## INSTALLATION METHOD FOR HEAD STUD KITS

Part Number: AR8696 Application: Yamaha YXZ - CA625+

1. **Always verify the part number for your application with the part number on the side of box and the part number on the instruction sheet. This will help ensure you have the correct installation procedure for your specific application before installing any components.**
2. Clean and inspect all hardware prior to installation. Look for obvious defects or shipping damages, plus proper fit, length and dimension.
3. To ensure proper thread engagement and accurate torque readings, clean ALL threads in the block. Chase if necessary with ARP Thread Chaser.
4. Screw studs into the block "HAND TIGHT ONLY".  
**NOTE: LOCTITE MAY BE USED IF A PERMANENT MOUNTING OF THE STUDS IS PREFERRED.**
5. Install the cylinder head(s) and check for binding or misalignment.
6. Lubricate the stud threads and nuts with ARP Ultra Torque lube (provided). Do not lubricate underside of washers. Then install the washers and the nuts onto the studs and tighten them hand tight. **ARP recommends using the ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT that is provided with each kit as opposed to motor oil. This is due to higher friction on the studs as well as inconsistencies in the clamping force of the fasteners when motor oil or other low quality lubricants are used.**

### TORQUE PROCEDURE

7. Following the manufacturers recommended torque sequence tighten the nuts in three equal steps to 65 ft lbs with **ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT.**

- |  |
|--|
| <ol style="list-style-type: none"> <li>1. Tighten nuts to 15 ft-lbs</li> <li>2. Tighten nuts to 30 ft-lbs</li> <li>3. Tighten nuts to 65 ft-lbs</li> </ol> |
|--|

ARP Ultra-Torque Fastener Assembly Lubricant has been specifically designed to reduce tension preload scatter and eliminate the need to cycle high performance engine fasteners before final installation. ARP Ultra-Torque far surpasses all requirements offered by previous ARP lubricants in terms of fastener preload repeatability and performance lubricating properties. For more information on ARP Ultra-Torque visit the ARP website at [www.arp-bolts.com](http://www.arp-bolts.com)